

12SP & 15SP

PUSH-AROUND STOCK PICKERS



Performance

Platform Height		
12SP	11 ft 9 in.	3.58 m
15SP	15 ft 2 in.	4.62 m
Working Height		
12SP	18 ft	5.49 m
15SP	21 ft	6.4 m
Drive Height		
Max. Platform Height		
Stowed Height	78 in.	198 cm
Platform Entry Height	17.5 in.	45 cm
Platform Size W x L	28 x 48 in.	71 x 122 cm
Overall Vehicle Length		
Stowed-12SP	72.5 in.	184 cm
Stowed-15SP	75.5 in.	192 cm
Overall Vehicle Width		
Stowed	34 in.	86 cm
Distance to Wall-Front		
0 in.	0 cm	
Distance to Wall-Side		
3 in.	7.6 cm	
Gross Vehicle Weight*		
DC Model-12SP	1,180 lb	535 kg
DC Model-15SP	1,240 lb	562 kg
Platform Capacity	500 lb	227 kg

* Certain options or country standards increase weight.



12SP

15SP

Standard Specifications

Power Source

Batteries	Sealed 100 amp-hr Glass Mat (AGM)
Battery Charger	5-Hour Automatic

Tires

Rear Wheels with Roller Bearings	10 in.	25 cm
Non-Marking Front Casters	6 in.	15 cm
Tire Material	Non-Marking	

Accessories & Options

- Folding Tray Platform
- Lifting Eye for a Crane Hook
- Battery Backed Emergency Lowering Control (mounted in platform)
- Extra Power Pack
- Programmable 4-Digit Security Lock
- Cycle Counter
- 110V Outlet
- 220V Outlet

Standard Features

- Low Maintenance Anodized Mast
- Fixed or Flexible Rail Set Up for Platform Access
- Hinged Gate for Unobstructed Front Entry
- Front and Side Entry Gates
- Removable Power Pack
- Dual Floor Brakes: One Per Side
- Safety Interlocked Controls
- 110V Double Receptacle in Platform
- Battery Discharge Indicator (BDI)
- Hourmeter
- Auto Power Saver—Shuts Off Power When Idle
- Key Lock Main Power Switch
- Manual Lowering Control at the Base
- Two Emergency Stop Controls—Platform and Base
- Transportation Tie Downs
- Built-In Fork Lift Pockets
- Lanyard Attachment Anchor
- Descent Alarm
- Flashing Amber Beacon
- ANSI, OSHA & CSA Compliant



The JLG "1 & 5" Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.

Part No: 3132138
R091801
Printed in USA

JLG Industries, Inc.
1JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

An Oshkosh Corporation Company